

# Battery for PSU (Power Supply Unit)

## PHTMPSU01

### Specifications

|   |     |
|---|-----|
| ➤ Nominal voltage (V)                       | 12  |
| ➤ 20-hr rate Capacity to 10.5V at 20°C (Ah) | 7   |
| ➤ 10-hr rate Capacity to 10.8V at 20°C (Ah) | 6.4 |

### Dimensions

|                              |           |
|------------------------------|-----------|
| ➤ Length (mm)                | 151 (±1)  |
| ➤ Width (mm)                 | 65 (±1)   |
| ➤ Height over terminals (mm) | 97.5 (±2) |
| ➤ Mass (kg)                  | 2.2       |

### Terminal Type

|  |      |
|--|------|
| ➤ FASTON - Quickfit / release (JST where stated) | 4.75 |
|--|------|

### Operating Temperature Range

|  |                |
|--|----------------|
| ➤ Storage (in fully charged condition) | -20°C to +60°C |
| ➤ Charge                               | -15°C to +50°C |
| ➤ Discharge                            | -20°C to +60°C |

### Storage

|   |   |
|---|---|
| ➤ Capacity loss per month at 20°C (% approx.) | 3 |
|---|---|

### Case Material

|                        |               |
|------------------------|---------------|
| ➤ Standard             | ABS (UL94:HB) |
| ➤ FR version available | UL94:V0       |

### Charge Voltage

|   |             |
|---|-------------|
| ➤ Float charge voltage at 20°C (V)/Block                      | 13.65 (±1%) |
| ➤ Float charge voltage at 20°C (V)/Cell                       | 2.275 (±1%) |
| ➤ Float Chg voltage tmp correction factor from std 20°C (mV)  | -3          |
| ➤ Cyclic (or Boost) charge Voltage at 20°C (V)/Block          | 14.5 (±3%)  |
| ➤ Cyclic (or Boost) charge Voltage at 20°C (V)/Cell           | 2.42 (±3%)  |
| ➤ Cyclic Chg voltage tmp correction factor from std 20°C (mV) | -4          |

### Charge Current

|  |          |
|--|----------|
| ➤ Float charge current limit (A)             | No limit |
| ➤ Cyclic (or Boost) charge current limit (A) | 1.75     |

### Maximum Discharge Current

|                |     |
|----------------|-----|
| ➤ 1 second (A) | 210 |
| ➤ 1 minute (A) | 48  |

### Impedance


|                          |    |
|--------------------------|----|
| ➤ Measured at 1 kHz (mΩ) | 23 |
|--------------------------|----|

### Design Life & Approvals

|   |                  |
|---|------------------|
| ➤ EUROBAT Classification: Standard Commercial | 3 to 5 years     |
| ➤ Yuasa design life at 20°C (yrs)             | up to 5          |
| ➤ VdS (Germany)                               | VdS No: G 189099 |



### Layout



### 3rd Party Certifications

ISO9001 - Quality Management Systems  
UNDERWRITERS LABORATORIES Inc.



### Safety

#### Installation

Can be installed and operated in any orientation except permanently inverted.

#### Handles

Batteries must not be suspended by their handles (where fitted).

#### Vent valves

Each cell is fitted with a low pressure release valve to allow gasses to escape and then reseal.

#### Gas release

VRLA batteries release hydrogen gas which can form explosive mixtures in the air. Do not place inside a sealed container.

#### Recycling

Each battery must be recycled at the end of life in accordance with local and national laws and regulations.